



## ANTI-GAWKING SCREENS

### Purpose /

ASKIN's anti-gawking screens are used to minimise visibility of construction activities to the travelling public and enable the safe and continuous passage of traffic through the construction site. ASKIN have a consistent level of success at meeting performance objectives for these screens.

### Standard Colour Options /

Surfmist, Paperbark and Pale Eucalypt.  
(Other colours are priced on application subject to MOQ.)  
Please find additional colour option brochures at [www.askin.net.au](http://www.askin.net.au).  
Printech Colour Range also available.

### Standard Profiles /

Flat, Rib, Silkline.

### Benefits /

- Cost effective, lightweight, functional and reusable.
- Screens can be easily maintained, removed and replaced when damaged or deteriorated with prolonged use.
- Will not present an undue risk to workers and other traffic during an impact.
- Ease of handling, installation, and removal in an emergency.

- Resistant to cyclic wind loading including buffeting from truck movements.
- Designed to withstand design wind loads without toppling, displacing or becoming detached from the barrier system to which it is attached.
- Contain no sharp edges, are not brittle or prone to become brittle and do not adversely affect or alter the performance of the barrier system.
- Product is neat, tidy, effective, robust and durable. Vertical alignment is achieved by correct use of stabilising wedges inside the stanchion holes.
- Height compliant - Minimum of 2.2 m total height and of sufficient extent to fully screen the work area from the public.
- Does not protrude or lean into vehicle path, especially when subject to wind loading.